

CLEANING

We recommend rinsing your GrowlerGasket and growler with warm water after each use. Allow both to dry.

AFTER THREE MONTHS...

You've been to plenty of breweries and it's time to give your treasured suds sealer a thorough clean!

Tools Needed:



Safety Glasses



Tiny Flat Blade Screwdriver

REMOVING THE GASKET

1. With safety glasses on, place supplied screwdriver against the back of the plastic insert at the designated notch (Figure 1A).
2. Pry the gasket away from the wall of the GrowlerGasket and lift up and out to remove completely (Figure 1B).
3. Wash* the gasket and the screw cap with mild warm detergent. Rinse both thoroughly while reminiscing about fresh beer you've recently enjoyed. Allow both to dry.



* Not dishwasher safe

REINSTALL THE GASKET

1. Bend gasket and place back end under the ring on the lower portion of the black threaded insert (Figure 1C).
2. Work the gasket around and under the entire ring of the insert pressing down with fingers.

REMOVING THE THREADED INSERTS (ANNUAL CLEANING)

1. With safety glasses on, remove the gasket as described above.
2. Once gasket has been removed, place supplied screwdriver in the notch on the GrowlerGasket's aluminum screwcap (Figure 2A).
3. Place your hand over the screw cap as shown (Figure 2B).
4. Pry plastic insert away from the back and pinch with fingers to remove. Remove the remaining half by pushing with your fingers (Figure 2C).
5. Clean both pieces of the plastic inserts, the gasket and the aluminum screwcap with warm, mild detergent. Rinse both thoroughly and allow to dry.



REINSTALL THE THREADED INSERTS (& GASKET)

1. Place the screw cap on its top. Take one of the insert halves, while making sure the extrusion is closest to you. With the slot on the aluminum screw cap facing you, install the insert making sure the extrusion snaps into the channel of the screw cap. Check again to make sure cut out slot is in this position with the insert (Figure 3B).
2. Next, take the other half of the insert and place ends against each other making sure the extrusion is closest to you.
3. Align and press the channel all the way to the other side where the two ends meet (Figure 3C). Using your finger, press back until you hear it snap into place (Figure 3D).
4. Reinstall the gasket (as described previously).
5. Wonderful beer is waiting—get out there and enjoy it! Your GrowlerGasket will keep it fresh!